

VKM74 / VKX74

Features and Strengths

- Multi-stage vacuum ejector
- Integrated pleated filter with high dirt capacity & Auto-cleaning system
- Quick response time
- Long life time
- Compact size and light weight



Specifications

Description	VKM74	VKX74
Max. Vacuum level	-85 kPa	-92 kPa
Open Vacuum flow	135 NI/min	109 NI/min
Max. Feed pressure	7 bar	7 bar
Temperature	-20 ~ 80 °C	-20 ~ 80 °C
Noise level	50 ~ 65 dbA	50 ~ 65 dbA
Weight	212 g	212 g

Vacuum Flow

Model	Max. vacuum (-kPa)	Vacuum flow (NI/min) at different vacuum levels (-kPa)									
		0	10	20	30	40	50	60	70	80	90
VKM74	85	135	99	62	54	40	32	24	9.6	2.64	-
VKX74	92	109	72	35	32	27	22	18	12	4.8	1.8

Evacuation Time

Model	Air Consumption (NI/min)	Evacuation time in sec / liter to reach different vacuum levels (-kPa)								
		10	20	30	40	50	60	70	80	90
VKM74	54 ~ 78	0.05	0.14	0.25	0.39	0.59	0.86	1.32	2.58	-
VKX74	66 ~ 88	0.06	0.2	0.38	0.6	0.89	1.23	1.72	2.54	4.8