


Screw-in connector

- Material stainless steel 1.4301/1.4307 (AISI 304/ 304L)
- Whitworth pipe thread
- Chambered O-ring
- Seals FKM
- Temperature range: -20 to +120 °C (-4 to 248 °F)
- Working pressure range: -0.95 to 16 bar (-14 to 232 psi)



Part no.	G	for tube	SW	i	L1	L2	D1	D2	NW	g/piece
928-0202	G1/8	OD4	13	7	21	10	8,6	14,2	3	9
928-0204	G1/8	OD6	13	7	23,5	12,5	11,5	14,2	5	10
928-0204X	G1/8	OD6	13	5,5	22	12,5	11,5	14,2	5	10
928-0206	G1/8	OD8	14	7	28,5	17,5	14,5	15,2	6	15
928-0208	G1/8	OD10	17	7	31,5	19	16,5	18,5	6	21
928-0295	G1/8	OD 3/8" (9,5)	17	7	31,5	19	16,1	18,5	6	21
928-0402	G1/4	OD4	17	9	23,5	10	8,6	18,5	3	18
928-0404	G1/4	OD6	17	9	26	12,5	11,5	18,5	5	19
928-0406	G1/4	OD8	17	9	29	15,5	14,5	18,5	6	21
928-0408	G1/4	OD10	17	9	33,5	20	16,5	18,5	8	23
928-0409	G1/4	OD12	19	9	39	23,5	20	20,7	8	36
928-0604	G3/8	OD6	22	9	27	12,5	11,5	23,8	5	33
928-0606	G3/8	OD8	22	9	30	15,5	14,5	23,8	6	35
928-0608	G3/8	OD10	22	9	32	17,5	16,5	23,8	8	35
928-0609	G3/8	OD12	22	9	34	19,5	20	23,8	9	37
928-0611	G3/8	OD14	22	9	41	26,5	22	23,8	11	45
928-0612	G3/8	OD16	24	9	45	28	24,9	26,2	10	59
928-0804	G1/2	OD6	24	11	29,5	12,5	11,5	26,2	5	51
928-0806	G1/2	OD8	24	11	32,5	15,5	14,5	26,2	6	54
928-0808	G1/2	OD10	24	11	34,5	17,5	16,5	26,2	8	53
928-0809	G1/2	OD12	24	11	36,5	19,5	20	26,2	9	54
928-0811	G1/2	OD14	24	11	38	21	22	26,2	11	52
928-0812	G1/2	OD16	24	11	45	27,5	24,9	26,2	12,5	64
928-0815	G1/2	OD20	30	11	61,2	39,2	30,5	33,5	15	123
928-1015	G3/4	OD20	32	12	61,2	38,2	30,5	34,8	16,5	145