

SUCTION CUPS / Flat & Curve

FCF40



Features and Strengths

Excellent for flat and curved material in both vertical and horizontal application
No vibration when transferring

Examples of use

Metal sheets, Car panel, Press metal sheets, Panel,
Electronic goods, Flat&curved glass



Recommended Lifting Force (Max.)

Model	Volume (cm ³)	Lifting Force (Kg) - Perpendicular			Lifting Force (Kg) - Parallel		
		- 20 kPa	- 60 kPa	- 90 kPa	- 20 kPa	- 60 kPa	- 90 kPa
FCF40	4.40	2.90	6.90	9.90	2.10	5.00	7.20

※ The lifting force above does not include safety factor

Material Specifications

Material	Hardness Shore (°)	Color	Temperature (°C)
NBR	60	Blue	-20~110
Silicone	55	Red	-70~200
Polyurethane	60	Translucent Orange	0~60


※ For additional material, see page 32~33

Material Resistance


Description	NBR	Silicone	Polyurethane
Wear Resistance	Excellent	Good	Excellent
Oil	Excellent	Poor	Excellent
Weather / Ozone	Fair	Excellent	Excellent
Alcohol	Good	Good	Fair
Acid	Fair	Poor	Fair

Dimension


[Unit : mm]




[With M10M fitting]




[With 18F fitting]




[With 14F fitting]



[With 14M fitting]




[With 38F fitting]



[With 38M fitting]



Build an Ordering No.

FCF40 -  : Pre-mounted fitting

1. Suction Cup

1. Suction cup	Description	Weight (g)	Symbol
	Flat-curve suction cup, 40mm diameter, Nitrile (NBR), M10xP1.5 male fitting	18.33	FCF40-N-M10M
	Flat-curve suction cup, 40mm diameter, Silicone, M10xP1.5 male fitting	17.15	FCF40-S-M10M
	Flat-curve suction cup, 40mm diameter, Polyurethane, M10xP1.5 male fitting	17.93	FCF40-PU-M10M
	Flat-curve suction cup, 40mm diameter, Nitrile (NBR), G1/8 female fitting	17.22	FCF40-N-18F
	Flat-curve suction cup, 40mm diameter, Silicone, G1/8 female fitting	14.72	FCF40-S-18F
	Flat-curve suction cup, 40mm diameter, Polyurethane, G1/8 female fitting	15.56	FCF40-PU-18F
	Flat-curve suction cup, 40mm diameter, Nitrile (NBR), G1/4 female fitting	26.3	FCF40-N-14F
	Flat-curve suction cup, 40mm diameter, Silicone, G1/4 female fitting	23.8	FCF40-S-14F
	Flat-curve suction cup, 40mm diameter, Polyurethane, G1/4 female fitting	24.64	FCF40-PU-14F
	Flat-curve suction cup, 40mm diameter, Nitrile (NBR), G1/4 male fitting	21.16	FCF40-N-14M
	Flat-curve suction cup, 40mm diameter, Silicone, G1/4 male fitting	18.66	FCF40-S-14M
	Flat-curve suction cup, 40mm diameter, Polyurethane, G1/4 male fitting	19.5	FCF40-PU-14M
	Flat-curve suction cup, 40mm diameter, Nitrile (NBR), G3/8 female fitting	25.26	FCF40-N-38F
	Flat-curve suction cup, 40mm diameter, Silicone, G3/8 female fitting	22.76	FCF40-S-38F
	Flat-curve suction cup, 40mm diameter, Polyurethane, G3/8 female fitting	23.6	FCF40-PU-38F
	Flat-curve suction cup, 40mm diameter, Nitrile (NBR), G3/8 male fitting	23.65	FCF40-N-38M
	Flat-curve suction cup, 40mm diameter, Silicone, G3/8 male fitting	21.15	FCF40-S-38M
	Flat-curve suction cup, 40mm diameter, Polyurethane, G3/8 male fitting	21.99	FCF40-PU-38M

