# **SUCTION CUPS** / VMECA Customized

## **KPS-5-15**







#### Features and Strengths

Developed to be used specially for bag opening application Suitable to be used in thin plastic and film type material

#### Examples of use

Plastic bag opening, Thin Film Material, Paper Bag Handling



### Recommended Lifting Force (Max.)

Model	Volume	Lifting Force (Kg) - Perpendicular		
	(cm³)	- 20 kPa	- 60 kPa	- 90 kPa
KPS-5-15	1.10	0.40	1.11	1.23

<sup>※</sup> The lifting force above does not include safety factor

## | Material Specifications


Material	Hardness Shore (°)	Color	Temperature (°C)	
NBR	60	Black	-20~110	
Silicone	55	Red	-70~200	
White Silicone	55	Translucent White	-70~200	
White Silicone (FDA)	55	Translucent White	-70~200	
High temp. Silicone	50	Blue	-70~280	
Conductive Silicone	70	Smoky Black	-45~90	
Urethane	rethane 60 Dark Green		0~100	

#### Material Resistance

Description	NBR	Silicone	White Silicone	High temp. Silicone	Conductive Silicone	Urethane
Wear Resistance	Excellent	Good	Good	Good	Good	Excellent
Oil	Excellent	Poor	Poor	Poor	Poor	Excellent
Weather / Ozone	Fair	Excellent	Excellent	Excellent	Excellent	Excellent
Alcohol	Good	Good	Good	Good	Good	Fair
Acid	Fair	Poor	Poor	Poor	Poor	Poor

#### Dimension

[Unit:mm]



[With 18F fitting]







## Build an Ordering No.




1. Suction cup	Description	Symbol	
	Customized suction cup, 15mm diameter, Nitrile (NBR)	KPS-5-15-N	
	Customized suction cup, 15mm diameter, Silicone	KPS-5-15-S	
	Customized suction cup, 15mm diameter, White silicone	KPS-5-15-WS	
	Customized suction cup, 15mm diameter, White silicone (FDA)	KPS-5-15-WS(FDA)	
	Customized suction cup, 15mm diameter, High temperature silicone	KPS-5-15-HS	
	Customized suction cup, 15mm diameter, Conductive silicone	KPS-5-15-CS	
	Customized suction cup, 15mm diameter, Urethane	KPS-5-15-U	
2. Fitting	Description	Symbol	
	Fitting, G1/8 female	18F	
	Fitting, G1/8 female, Mesh filter	M-18F	

## Spare Parts - Rubber Parts

Part No.	Description	Weight (g)	Color
KPS-5-15-N	Customized suction cup, 15mm diameter, Nitrile (NBR)	6.17	Black
KPS-5-15-S	Customized suction cup, 15mm diameter, Silicone	5.89	Red
KPS-5-15-WS	Customized suction cup, 15mm diameter, White silicone	5.85	Translucent White
KPS-5-15- WS(FDA)	Customized suction cup, 15mm diameter, White silicone (FDA)	5.85	Translucent White
KPS-5-15-HS	5-HS Customized suction cup, 15mm diameter, High temperature silicone		Blue
KPS-5-15-CS	Customized suction cup, 15mm diameter, Conductive silicone	6.35	Smoky Black
KPS-5-15-U	Customized suction cup, 15mm diameter, Urethane	6.39	Dark Green

## [Unit:mm]



## Spare Parts – Fittings

Part No. (Code No.)	Fitting size	Description	Weight (g)	
350 000 3351	18F	G1/8 female	16.22	
350 000 4351	18F-F	G1/8 female, Mesh filter	16.26	