

SUCTION CUPS / Sponge

VS400

Features and Strengths

Excellent performance for rough and uneven surfaces

Examples of use

Marbles, Paving Slabs, Bricks, Rough Wood, Masonry



Recommended Lifting Force (Max.)

Model	Volume(cm ³)	Lifting Force (Kg) - Perpendicular		
		- 20 kPa	- 60 kPa	- 90 kPa
VS400	2288.00	326.00	876.00	1300.00

※ The lifting force above does not include safety factor

Material Specifications


Material	Hardness Shore (°)	Color	Temperature (°C)
EPDM	40°	Black	0~150

Material Resistance


Description	EPDM
Wear Resistance	Fair
Oil	Poor
Weather / Ozone	Excellent
Alcohol	Excellent
Acid	Poor

Dimension

[Unit : mm]



I Build an Ordering No.



1. Suction cup	Description	Symbol
	Sponge suction cup, 400mm diameter, EPDM	VS400-E

2. Fitting	Description	Symbol
	Fitting, G3/4 female	34F

I Spare Parts – Rubber Part

Part No.	Description	Weight (g)	Color
VS400-E	EPDM Perimeter Seal	350	Black

I Spare Parts – Fittings

Part No. (Code No.)	Fitting size	Description	Weight (g)
350 001 3718	34F	G3/4 female	3016